



## Flexibility

As with all of our purpose-built terminals, the Z8 supports various Windows operating systems (OS). Connectivity is incredibly varied and simple with a range of multiple port formats included to support a variety of peripheral hardware including cash drawers, receipt printers, Chip and PIN devices and barcode scanners.

## Design

The high quality finish has been crafted to complement all modern hospitality venues, with a range of mounting options and accessories, the Z8 will look at home in any environment.

## Reliability

We recognise that downtime on a unit can effect your business, so the terminal is designed to withstand the pressures of a fast-paced hospitality environment. The passive cooling system is fanless, avoiding moving parts and their inherent reliability risk.

## Ease of Service and Maintenance

Ensuring we keep your business running is a top priority, so the Z8 is designed with ease of servicing and rapid maintenance in mind. Key components can be replaced quickly and easily without data loss, and complete unit swapping is equally effective with this terminal.

## Environmentally Friendly

As with all of our terminals, the Z8 comes with all of the functionality you'd expect of a terminal ready to deal with every aspect of the hospitality industry. Connecting to a wide variety of peripheral hardware, including cash drawers, receipt printers, Chip and PIN devices and barcode scanners, it's one of the most versatile terminals on the market today.

Interfaces
1 x DC input 12V
1 x Powered USB 24V
1 x Cash Drawer (12V or 24V) switchable
1 x Giga LAN
1 x VGA for 2nd Monitor
4 X USB Ports (USB 3.0 x 1: USB2.0 x 3)
1 x RJ45 / Com1 (R1/5V/12V)
1 x DC output 12V
2 x DB9 (Com2, Com4, RI, 5V, 12V Selectable)

## Features

- 15" True-Flat PCAP screen
- Aluminium Die-Casting + Plastic body – Black with Silver Trim
- VESA 100 x 100mm mounting
- 2x 2W Internal Speakers
- 4GB memory standard, max 8GB (1 x 204-pin DDR3L)
- 1 x 2.5" SATA HDD or SSD

## Optional Features

- MSR & iButton reader
- Choice of integrated customer display screens



Technical Specifications	
Dimensions	Product: 366 x 334 x 220 mm Carton: 480 x 460 x 320 mm
Weight	Net: 4.9 Kg Gross: 8 Kg
Temperature	Operation: 0°C ~ 40°C (32°F ~ 104°F) Storage: -20°C ~ 60°C (-4°F ~ 130°F)
Display	15" TFT, 1024 x 768
Operating system	POSReady 7 POSReady 2009 Windows 10 Pro Windows 10 IoT Enterprise
Power	12V / 90W External Adapter 12V / 150W External Adapter
Certification	FCC / CE Class B

Give us a call today . . .

**0800 131 3400**

or drop us an email . . .

**sales@zonal.co.uk**